

Nautic Rib

Interface

SPECIFICATION

Product Definition	ISO 2424	Fibre bonded carpet tile
Fibre Material	Directive 71/307/CEE	72 % Polypropylene / 27.5% Nylon/ 0.5% A.S. Fibre
Fibre Weight	ISO 8543	770 g/m ² ± 5 %
Total Thickness	ISO 1765	7.0 mm ± 0.5 mm
Total Weight	ISO 8543	4250 g/m ² ± 10%
Backing Type	ISO 3018	Graphlar
Tile Size		50 x 50 cm ± 0.3 %
Tiles per Box		20
Style Number		6900700004
Recommended Installation		Quarterturn

PERFORMANCE

Use Classification	EN 13297	Class 31 Moderate Contract Use
--------------------	----------	--------------------------------

ELECTROSTATIC PROPERTIES

Walk on Test	ISO 6356	Max. 2.0 KV
--------------	----------	-------------

FLAME PROPERTIES

Hot Metal Nut (UK)	BS 4790	Pass, low radius of effects of ignition
Radiant Panel	EN 13501-1	Cfl - s1 Rating

COLOUR FASTNESS PROPERTIES

Light	ISO 105 BO2	≥6-7
Rubbing Dry	ISO 105 X12	≥3-4
Wet	ISO 105 X12	≥3-4
Carpet Shampoo	BS 1006	≥3-4
resistance to Moths and Beetles		100 %